

Geberit Sales Ltd  
Geberit House  
Edgehill Drive  
Warwick  
CV34 6NH

T 01926 516800  
F 01926 400101  
E [enquiries@geberit.co.uk](mailto:enquiries@geberit.co.uk)

Literature 0800 007 5133

→ [www.geberit.co.uk](http://www.geberit.co.uk)

**■ GEBERIT**

GEBERIT MEPLA

**EASY TO HANDLE**



GEB-DEV-01-2018

**KNOW  
HOW  
INSTALLED**

# FLEXIBLE, RELIABLE, SAFE AND EASY TO PROCESS

→ COMBINES THE ADVANTAGES OF PLASTIC AND METAL

→ CORROSION-RESISTANT

→ EXTENSIVE ASSORTMENT WITH 8 PIPE DIMENSIONS AND 300 FITTINGS

→ SIMPLE PROCESSING



## ↑ LEAKY IF UNPRESSED

Unpressed Geberit Mepla fittings leak visibly when subjected to leak tests with water. Water flows out of the unpressed connections. This occurs even at low water testing pressure and during leak tests at up to 15 bar. The pressure test cannot be completed successfully unless all the connections have been pressed.

## CONNECTIONS WITH TRIPLE RELIABILITY

Geberit Mepla offers triple safety. The insertion depth is visible and unmistakably indicates the correct position of the fitting on the pipe. A tool guide rim ensures that the pressing tool is correctly positioned. Defined leak paths also ensure that fittings which have not yet been pressed can be clearly detected during the leak test.



## IDEAL FOR COLD WATER PIPES

Cooling pipes can be installed with Geberit Mepla without too much effort, as special processing is not required for corrosion protection.

## LARGE DIAMETER

Geberit Mepla is available up to a dimension of d75 and can therefore be used in a broad range of applications. Larger construction projects can consistently be installed with Geberit Mepla.

## LIGHTWEIGHT

Mepla comes in 100m which is easily transportable compared to copper.

## ← PRESSING JAW GUIDE

The defined jaw guide on the fitting ensures that the pressing jaw is positioned exactly right during pressing and can not slip. This prevents failed pressing sequences which therefore guarantees a secure, long-lasting connection.



## ↑ RELIABLE INSERTION DEPTH CONTROL

The insertion depth remains visible at all times. This ensures that the pipe is correctly pushed onto the fitting during installation and can then be correctly pressed. The piping system can therefore be pre mounted. When the system is ready to be pressed, each connection can be checked immediately to ensure that each pipe is in the correct position.



## ↑ EASY AND RELIABLE INSTALLATION

Special cams on the plastic fittings and retaining rings on the metal fittings achieve a high level of fitting, retaining force in the pipe and prevent the fitting slipping out of the pipe during installation. The pipe system is therefore easy to install, align and then press.

## FEWER FASTENING POINTS

The special composition of Geberit Mepla pipes with the thick aluminium layer reduces the extent to which the pipes expand in response to temperature fluctuations. This means fewer fastening points are required during installation than with conventional plastic pipes.

